

LATEX-ITE NEUTRAL BASE FILLER

PRODUCT SPECIFICATIONS

DESCRIPTION AND USAGE

LATEX-ITE NEUTRAL BASE FILLER is a non pigmented, 100% acrylic latex compound for new or previously sealed bituminous concrete tennis courts. Neutral Base Filler is intended for use in leveling and resurfacing bituminous concrete tennis courts. It can be mixed to serve (2) purposes:

1. Use as a non pigmented texture course to be applied prior to the application of Latexite Color
2. Use as a component to Fortified (RTU) ready-to-use Latexite Color

PHYSICAL PROPERTIES

Color: Grey	To the touch: To top-coat:	30 min. - 1 hour 8 hours
Weight per gallon: 8.8 lbs.	Minimum ambient, surface and product installation temperature: 50°F and rising	
Drying time @ 70°F & 50% relative humidity*	*Low temperatures and high humidity will increase drying time dramatically. Maximum surface temperature = 140°F.	

Surface Condition

The surface upon which Latexite Neutral Base Filler is to be applied must be smooth, free of dirt, loose or flaking paint, oily materials or chemical residues, vegetation or any other foreign matter that may prevent the proper bonding.

Prior to application of Latexite Neutral Base Filler, the court surface shall be flooded with water and allowed to drain. Any depressions capable of submerging a U.S. five cent piece after one hour should be marked and repaired.

Mix Design

The following mix design has been found to be satisfactory for most surface conditions. The mix may be varied to suit individual job requirements through modification of silica sand and water.


Leveling Mix	
PLUSH™ ACRYLIC RESURFACER 2000-27	55 gal.
Silica Sand (80-100 mesh)	700 lbs.
Clean potable water	5-20 gal.

Resurfacing Mix	
PLUSH™ ACRYLIC RESURFACER 2000-27	55 gal.
Silica Sand (80-100 mesh)	500-700 lbs.
Clean potable water	20-40 gal.

After the addition of Neutral Base Filler concentrate, thorough mixing is required. A mechanical mixer is recommended and the mixture should be stirred until homogeneous. Periodic mixing should take place as the job progresses to ensure consistent application.

CAUTION

HARMFUL IF SWALLOWED



131 Willow St. Cheshire, CT 06410

203.272.3221

Toll Free 888.711.7483

Fax 203.271.3396