



MATERIAL SAFETY DATA SHEET

Name of Material Super Patch	
1	HEALTH
1	FLAMMABILITY
0	REACTIVITY
J	PROTECTIVE EQUIPMENT

Section I - PRODUCT IDENTIFICATION

PRODUCT NAME: Latexite[®] Pothole Patch
MANUFACTURER NAME: Dalton Enterprises, Inc.
ADDRESS: 131 Willow Street Cheshire, CT 06410
EMERGENCY PHONE NUMBER: (203) 272-3221
AFTER 5 PM AND ON WEEKENDS: (203) 272-3221
ORIGINATOR: K.P.
TRADE NAMES & SYNONYMS: Pavement Patch
CHEMICAL FAMILY: Mixture
EFFECTIVE DATE: 02/25/2008
DATE SUPERSEDED: 01/10/2006

Section II - HAZARDOUS / NON-HAZARDOUS INGREDIENTS

Asphalt

CAS #8052-42-4
 Listed in SARA Title III, Section 313: No
 OSHA PEL: 10 ppm
 ACGIH TLV: 0.2 mg/m³ (volatiles)
 STEL: N/A
 LC50: N/A
 LD50 N/A

Lime Stone

CAS #1317-65-3
 Listed in SARA Title III, Section 313: No
 OSHA PEL: N/A
 ACGIH TLV: N/A
 STEL: N/A
 LC50: N/A
 LD50: CTI > 320,000

N/A = Not available or applicable

Ingredients total weight % are below 100% only if all others unlisted are not considered hazardous by any federal (OSHA, WHMIS, SARA), any state or province, or local Right-To-Know regulations.

Section III - PHYSICAL DATA

APPEARANCE & ODOR: Black viscous fluid mixed with sand and stone. Asphaltic odor.

BOILING POINT: 900°F

VAPOR PRESSURE: N/A

SPECIFIC GRAVITY: 1.3

SOLUBILITY IN WATER: negligible

EVAPORATION RATE: Not Known

PH: N/A

WATER/OIL DIST. COEFFICIENT:

MAX VOC: Less than 10g/L

PHYSICAL STATE: Solid

FREEZING POINT: N/A

% VOLATILE (by Wt.): negligible

THRESHOLD ODOR: N/A

VAPOR DENSITY: (air+)GT10

Section IV - FIRE AND EXPLOSION HAZARD DATA

FLAMABILITY CLASSIFICATION: Not Regulated

FLASH POINT: Greater than 210°F. TCC

AUTO IGNITION TEMP.: N/A

LOWER EXPLOSIVE LIMIT (LEL): N/A

UPPER EXPLOSIVE LIMIT (UEL): N/A

COMBUSTION PRODUCTS:

Hydrocarbon compounds, CO₂ and CO.

EXTINGUISHING MEDIA:

Water, foam and dry chemical

SPECIAL FIRE FIGHTING PROCEDURES:

Firefighters should wear self-contained breathing equipment in addition to normal personal protective equipment. Do not allow run off from fire fighting procedures to enter public waterways.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Closed containers may build pressure from heat. Dust residues can potentially form explosive mixtures with air. Use adequate ventilation with clean-up procedures. Burning liquid can float on water and spread further.

NFPA RATING: HEALTH: 1 FIRE: 1 REACTIVITY: 0

UN/NA/PIN#: N/A

IMPACT SENSITIVE: No

STATIC SENSITIVE: No

EXPLOSIVE POWER: N/A

BURNING RATE: N/A

Section V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section II

ROUTES OF ENTRY: Skin, eyes, inhalation, ingestion.

EFFECTS OF OVEREXPOSURE / ACUTE OVEREXPOSURE:

Eyes: May cause severe eye irritation which can result in irreversible damage.

Inhalation: May cause headaches, dizziness, nausea vomiting and perhaps loss of consciousness. Vapors may be irritating to eyes, nose and throat.

Skin: May cause irritation of skin and/or systemic effects by absorption.

Ingestion: May result in vomiting; aspiration of vomitus must be avoided as liquid contact with the lungs can result in chemical pneumonitis and pulmonary edema/hemorrhage. Have patient drink large amounts of water; contact a physician.

UNUSUAL CHRONIC TOXICITY:

Prolonged or repeated contact over many years in the absence of good hygiene and personal protection may lead to changes in skin pigmentation and skin tumors and cancer of the skin, lungs, kidney or bladder.

EMERGENCY AND FIRST AID PROCEDURES:

Eyes: Immediately flush with clean water for 15 minutes while holding eyelids open; consult a physician.

Inhalation: If overcome by mist or vapor, remove from exposure immediately; call a physician. If breathing is stopped or irregular, start resuscitation, administer oxygen.

Skin: Remove any contaminated clothing and wash skin with soap and warm water. Vegetable or mineral oil can remove dry material.

Ingestion: DO NOT INDUCE VOMITING even though vomiting may occur. If vomiting occurs,

keep head below hips to prevent aspiration of liquid into the lungs. Get immediate medical attention.

Section VI - REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Keep from freezing.

INCOMPATIBILITY (materials to avoid): Strong oxidizing agents.

HAZARDOUS POLYMERIZATION: Will Not Occur

HAZARDOUS DECOMPOSITION PRODUCTS: N/A

CONDITIONS TO AVOID: High temperatures. Keep product from freezing.

Section VII - SPILL OR LEAK PROCEDURES

SARA TITLE III:

#302: No #304 CERCLA: No #313: No RCRA: No

Steps to be taken in case material is released or spilled:

Ventilate the area. Wear suitable protective clothing, gloves and eye/face protection. Contain and pick up waste materials. Put in a sealed, approved container. Dispose of in accordance with federal, state and local regulations.

Reportable Quantity (lb.): N/A

TPO (lb.): N/A

Regulations: WHMIS, SARA, state and province.

Hazardous Waste: None.

Section VIII - SAFE HANDLING AND PROTECTION INFORMATION

Respiratory Protection: Use only with adequate ventilation. If ventilation is inadequate, wear approved respiratory equipment.

Ventilation:

Local Exhaust: Required

Mechanical (general): Required

Special: N/A

Other: N/A

Protective Gloves: Rubber gloves

Eye Protection: Wear safety glasses, goggles or face shield.

Other Protective Equipment: Wear suitable protective clothing.

Estimated LD50, MG/KG: N/A

Estimated LC50, MG/KG: N/A

Sensitization: N/A

Section IX - SPECIAL PRECAUTIONS

Keep out of reach of children.

Always read label plus precautions and follow directions carefully.

Keep from freezing.

Do not breathe vapor or spray mist.

Use only with adequate ventilation.

Do not take internally.

Avoid contact with eyes and skin.

Wash thoroughly after using.

Additional Technical Data Sheets and/or MSDS are available upon request.

THE INFORMATION AND RECOMMENDATIONS PROVIDED HEREIN ARE BELIEVED TO BE ACCURATE AS OF THE DATE HEREOF. HOWEVER, SUCH INFORMATION AND RECOMMENDATIONS ARE PROVIDED WITHOUT WARRANTY OF ANY KIND AND THIS CORPORATION DISCLAIMS ANY AND ALL LIABILITY OR LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON SAME.